

OCEANAIRE

MODEL: PAC2412
2 TON SPOT COOLER

TECHNICAL SPECIFICATIONS



AIR COOLED



WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE
OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT
PLUS, 4 ADDITIONAL YEARS FOR THE COMPRESSOR
(RESTRICTIONS APPLY)

| | |
|----------------------------|--------------------------------|
| COOLING CAPACITY | 24,020 BTUH |
| VOLTAGE | 208-230 V, 60 Hz, Single Phase |
| AMPS | 14.9 A |
| WATTS | 2700 W |
| IN RUSH AMPS | 68 A |
| EER | 8.9 |
| COMPRESSOR TYPE | ROTARY |
| COMPRESSOR MOTOR | 2 HP |
| COMPRESSOR RLA | 10.5 A |
| COMPRESSOR LRA | 48 A |
| EVAPORATOR BLOWER | CENTRIFUGAL |
| EVAP CFM - HIGH | 810 |
| EVAP MOTOR HP | 1/3 HP |
| CONDENSER BLOWER | CENTRIFUGAL |
| COND CFM | 1010 |
| COND MOTOR HP | 1/3 HP |
| POWER CORD | 14/3 |
| PLUG TYPE | 6-20P, LCDI |
| CORD LENGTH | 10 FT |
| CONDENSATE REMOVAL SIZE | TANK 5 GALLON |
| REFRIGERANT CHARGE | 37 OZ., R-410A |
| HEIGHT W/ CASTERS | 45-3/4 in |
| HEIGHT W/O CASTERS | 40-1/2 in |
| WIDTH | 24 in |
| DEPTH | 30 in |
| NET WEIGHT | 260 lb. |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed, with condenser discharge air ducted into another area
- OA CFM with free discharge
- OA Amps & Watts at 208 Volts

COOLING AMBIENT OPERATING RANGE 65° TO 105°

NOT APPROVED FOR OUTDOOR USE



OA-TS-PAC2412-07262018

OCEANAIRE
OCEANAIRE-INC.COM



MODEL: PAC2412
2 TON SPOT COOLER

FEATURES:

- OA 24 V CONTROL CIRCUIT WITH NON-PROGRAMMABLE ELECTRONIC THERMOSTAT
- OA WASHABLE ELECTROSTATIC AIR FILTER
- OA SWIVEL BALL BEARING CASTERS WITH LOCKS AT FRONT
- OA 2-SPEED FAN SWITCH
- OA CONDENSATE TANK ALERT LIGHT
- OA LCDI POWER CORD
- OA HIGH PRESSURE SAFETY SWITCH

