

TECHNICAL SPECIFICATIONS

MODEL: 20AC	1211	1811	2412	3612	3632	3634	6012	6032	6034
COOLING CAPACITY	11,800	16,800	24,020	36,050			60,100		
VOLTAGE (V/Phase) at 60Hz	115/1		208-230/1		208-230/3	460/3	208-230/1	208-230/3	460/3
AMPS	10.4	14.1	14.9	19.6	17.2	8.7	32	20.4	14.8
TOTAL WATTS	1180	1670	2700	3620			6000		
IN-RUSH AMPS	60	75	68	113	93	60	178	162	87
PLUG TYPE	5-15P LCDI	5-20P LCDI	6-20P LCDI	6-30P LCDI	L15-30P	L16-20P	6-50P	L15-30P	L16-20P
EER	10.0		8.9	10.0					
COMPRESSOR	ROTARY	ROTARY	ROTARY	SCROLL			SCROLL		
COMPRESSOR HP	1	1.5	2	3	3	3	5	5	5
COMPRESSOR LRA	50	63	48	83	77	35	158	137	52
EVAPORATOR CFM - HIGH	400	600	810	1200			1950		
EVAPORATOR MOTOR HP	1/8		1/3			1			
CONDENSER CFM	580	930	1010	1390			2200		
CONDENSER MOTOR HP	1/8		1/3	1					
CONDENSATE TANK	5 Gallon - STANDARD (Pump Optional)						Pump - STANDARD (20 ft. Lift)		
R-410A CHARGE (oz.)	18	40	37	66			80		
HEIGHT (in.)	37-3/4	45-3/4		50-1/4			51-3/4		
WIDTH (in.)	20	24		27-1/2					
DEPTH (in.)	25	30		35			39-1/2		
NET WEIGHT (lb.)	180	260		365		400	485		520

20ACSPES05012020

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- OA Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- OA EER is determined at high fan speed, with condenser discharge air ducted into another area
- OA CFM with free discharge


COOLING AMBIENT OPERATING RANGE 65° TO 105°

NOT APPROVED FOR OUTDOOR USE



PRODUCT FEATURES


- OA SOLID STATE ELECTRONIC CONTROLLER
- OA MANUAL OR AUTO 6-SPEED FAN CONTROL
- OA LARGE LED DISPLAY
- OA SWIVEL BALL BEARING CASTERS WITH LOCKING FRONTS
- OA CONDENSATE OVERFLOW ALERT
- OA LCDI POWER CORD (SOME MODELS)
- OA HIGH PRESSURE SAFETY SWITCH
- OA WASHABLE ELECTROSTATIC AIR FILTERS
- OA THREE PHASE MONITOR (SOME MODELS)



CONDENSATE PUMP KIT
 for Unattended Operation


2DPC-1 115V for size 12, 18
 2DPC-2 230V for size 24, 36

Optional ACCESSORIES




NOZZLE KIT
 for Directional Cooling/Heating

2NK-1 2 x 4" for size 12
 2NK-2 2 X 6" for size 18, 24
 2NK-3 2 X 8" for size 36, 60



DISCHARGE DUCT ADAPTER
 for Extended Single Duct Length

2DDA-6 6" for size 12
 2DDA-10 10" for size 18, 24
 2DDA-16 16" for size 36, 60



EVAPORATOR RETURN AIR PLENUM

DEP-10 10" for size 12
 2DEP-12 12" for size 18, 24
 DEP-16 16" for size 36, 60

Cooling done Right!

OCEANAIRE

OCEANAIRE-INC.COM

OA-TS-20ACSERIES-05012020