

MODEL: 2OAC1211

1 TON DELUXE PORTABLE SPOT COOLER – AIR COOLED



AIR COOLED

COOLING CAPACITY 11,800 BTUH

VOLTAGE 115V, 60Hz, 1PH
 AMPS 10.4 A
 TOTAL WATTS 1180 W

IN RUSH AMPS 60 A
 PLUG TYPE 5-15P, LCDI
 EER 10.0

COMPRESSOR HP 1
 COMPRESSOR RLA 9.5
 COMPRESSOR LRA 50

EVAP CFM - HIGH 400
 EVAP MOTOR HP 1/8

COND CFM 580
 COND MOTOR HP 1/8 HP

CONDENSATE TANK 5 GALLON
 (Pump Optional)

REFRIGERANT CHARGE 18 oz R-410A

HEIGHT 37-3/4 in
 WIDTH 20 in
 DEPTH 25 in

NET WEIGHT 180 lb



WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT PLUS, 4 ADDITIONAL YEARS FOR THE COMPRESSOR (RESTRICTIONS APPLY)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- ⓘ **Cooling Capacity** is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- ⓘ Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- ⓘ EER is determined at high fan speed, with condenser discharge air ducted into another area
- ⓘ CFM with free discharge
- ⓘ Amps & Watts at 115 Volts

COOLING AMBIENT OPERATING RANGE 65° TO 105°



NOT APPROVED FOR OUTDOOR USE

PRODUCT FEATURES

- OA SOLID STATE ELECTRONIC CONTROLLER
- OA MANUAL OR AUTO 6-SPEED FAN CONTROL
- OA LARGE LED DISPLAY
- OA REAR SWIVEL CASTERS
- OA FRONT SWIVEL CASTERS WITH BRAKES
- OA CONDENSATE ALERT
- OA LCDI POWER CORD
- OA HIGH PRESSURE SAFETY SWITCH
- OA WASHABLE ELECTROSTATIC AIR FILTERS

MODEL: 20AC1211

1 TON DELUXE PORTABLE SPOT COOLER



ACCESSORIES

