

OCEANAIRE

MODEL: 2OAC6012
5 TON DELUXE PORTABLE
AIR CONDITIONER

TECHNICAL SPECIFICATIONS

COOLING CAPACITY	60,100 BTUH
VOLTAGE	208-230V, 60Hz, 1PH
AMPS	32
TOTAL WATTS	6000
IN RUSH AMPS	178
PLUG TYPE	6-50P
EER	10.0
COMPRESSOR	SCROLL
COMPRESSOR HP	5
COMPRESSOR LRA	158
EVAP CFM - HIGH	1950
EVAP MOTOR HP	1
COND CFM	2200
COND MOTOR HP	1
CONDENSATE REMOVAL	PUMP – 20' LIFT
REFRIGERANT CHARGE	80 oz R-410A
HEIGHT	51-3/4 in
WIDTH	27-1/2 in
DEPTH	39-1/2 in
NET WEIGHT	485 lb

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

- OA **Cooling Capacity** is total BTUH at 80°DB/67°WB return air
95°F Outdoor at high fan speed
- OA Dedicated Circuit and Time Delay fuses/circuit breakers
are recommended
- OA EER is determined at high fan speed, with condenser
discharge air ducted into separate area
- OA CFM with free discharge
- OA Amps & Watts at 208 Volts

COOLING AMBIENT **OPERATING RANGE 65° TO 105°**

NOT APPROVED FOR OUTDOOR USE



AIR COOLED




Cooling done Right!
OCEANAIRE


OCEANAIRE-INC.COM
OA-TS-2OAC6012-02112021

PRODUCT FEATURES


- OA SOLID STATE ELECTRONIC CONTROLLER
- OA MANUAL OR AUTO 6-SPEED FAN CONTROL
- OA LARGE LED DISPLAY
- OA SWIVEL BALL BEARING CASTERS WITH LOCKING FRONTS
- OA CONDENSATE OVERFLOW ALERT
- OA HIGH PRESSURE SAFETY SWITCH
- OA WASHABLE ELECTROSTATIC AIR FILTERS




Optional ACCESSORIES



**2NK-3 (2 X 8")
NOZZLE KIT**
for Directional
Cooling/Heating



**2DDA-16
DISCHARGE
DUCT ADAPTER**
for Extended
Single Duct Length



**DEP-16
EVAPORATOR RETURN
AIR PLENUM**