

PROVIDING A BETTER CLIMATE ANYWHERE.







5 Ton Deluxe Portable Heat Pump

Product Features:

- Solid State Electronic Controller
- Automatic Mode Changeover
- Manual or Auto 6-Speed Fan Control
- Large LED Display
- Swivel Ball Bearing Casters with Locking Fronts
- Condensate Overflow Alert
- High Pressure Safety Switch
- Three Phase Monitor
- Washable Electrostatic Air Filters

Technical Specifications:

Specifications subject to change without notice

Cooling Capacity: 60,100 BTUH Heating Capacity: 53,500 BTUH

Voltage: 208-230V, 60Hz, 3PH

Amps: 20.4 Total Watts: 6000

Cooling Ambient: Operating Range

65° to 105°

Heating Ambient: Operating Range

40° to 85°

Outdoor Use: No

Cooling Capacity: Total BTUH at

80°DB/67°WB

Return Air 95°F Outdoor

at High Fan Speed.

Heating Capacity: Total BTUH at

70°DB/60°WB Indoor, 47°DB/43°WB Outdoor

 In Rush Amps:
 162

 Plug Type:
 L15-30P

 EER:
 10.0

NOTE: Dedicated circuit and time delay fuses /

circuit breakers are recommended.

Compressor:	Scroll
Compressor HP:	5
Compressor LRA:	137
EVAP CFM - High:	1950
EVAP Motor HP:	1
COND CFM	2200
COND MOTOR HP	1
Condensate Removal:	Pump Automatic
	20' Vertical Lift
Refrigerant Charge:	80 oz R-410A
Height:	54.2″
Width:	28.2"
Depth:	41.0"
Net Weight:	485 lbs.






Optional Accessories



Ceiling Panel Kit
For discharging the condenser
air above a drop ceiling
Part Number: CK-16



Nozzle Kit / 2 x 8"
For directional cooling
Part Number: 2NK-3



Evaporator Return Air PlenumFor ducting return air
Part Number: DEP-16




Discharge Duct AdapterFor extended duct length
Part Number: 2DDA-16



OCEANAIRE PROVIDING A BETTER CLIMATE ANYWHERE.

OceanAire, Inc. 1731 Wall Street, Suite 100 Mount Prospect, Illinois 60056

OA-TS-2OACH6032-01.03.22



inlet of the condenser.
Part Number: DCP-5

