

PROVIDING A BETTER CLIMATE ANYWHERE.







2 Ton Deluxe Portable Heat Pump

Product Features:

- Solid State Electronic Controller
- Automatic Mode Changeover
- Manual or Auto 6-Speed Fan Control
- Large LED Display
- Swivel Ball Bearing Casters with Locking Fronts
- Condensate Overflow Alert
- High Pressure Safety Switch
- Washable Electrostatic Air Filters

Technical Specifications:

Specifications subject to change without notice

Cooling Capacity: 24,020 BTUH Heating Capacity: 22,000 BTUH

Voltage: 208-230V, 60Hz, 1PH

Amps: 14.9 Total Watts: 2700

Cooling Ambient: Operating Range

65° to 105°

Heating Ambient: Operating Range

40° to 85°

Outdoor Use: No

Cooling Capacity: Total BTUH at

80°DB/67°WB

Return Air 95°F Outdoor

at High Fan Speed.

Heating Capacity: Total BTUH at

70°DB/60°WB Indoor, 47°DB/43°WB Outdoor

In Rush Amps: 68

Plug Type: 6-20P, LCDI

EER: 8.9

NOTE: Dedicated circuit and time delay fuses /

circuit breakers are recommended.

Compressor: Compressor HP: Compressor LRA:	Rotary 2 48
EVAP CFM - High: EVAP Motor HP:	810 1/3
COND CFM COND MOTOR HP	1010 1/3
Condensate Tank: Pump Optional	5 Gallon
Refrigerant Charge:	37 oz R-410A
Height: Width: Depth: Net Weight:	46.7" 24" 31.5" 260 lbs.









Ceiling Panel Kit
For discharging the condenser
air above a drop ceiling
Part Number: CK-12



Nozzle Kit / 2 x 6" For directional cooling Part Number: 2NK-2



Evaporator Return Air PlenumFor ducting return air
Part Number: 2DEP-12



Discharge Duct AdapterFor extended duct length
Part Number: 2DDA-10



Universal Condensate Pump KitFor unattended operation
Part Number: UPK-230



Condenser Return Air Plenum
For installations where it is required to duct air to the inlet of the condenser.
Part Number: 2DCP-2



OceanAire, Inc. 1731 Wall Street, Suite 100 Mount Prospect, Illinois 60056

OA-TS-2OACH2412-01.03.22

