





AIR COOLED



1.5 TonPortableAir Conditioner

Product Features:

- 24V Control Circuit with Non-Programmable Electronic Thermostat
- Swivel Ball Bearing Casters with Locking Fronts
- 2-Speed Fan Switch
- Condensate Overflow Alert Light
- High Pressure Safety Switch
- Washable Electrostatic Air Filters

Technical Specifications:

Specifications subject to change without notice

Cooling Capacity: 16,800 BTUH
Voltage: 115V, 60Hz, 1PH

Amps: 14.1 Total Watts: 1670

Cooling Ambient: Operating Range

65° to 105°

Outdoor Use: No

Cooling Capacity: Total BTUH at 80°DB/67°WB

Return Air 95°F Outdoor at High Fan Speed.

In Rush Amps: 75

Plug Type: 5-20P, LCDI EER: 10.0

NOTE: Dedicated circuit and time delay fuses /

circuit breakers are recommended.

Compressor: Compressor HP:	Rotary 1 1/2	
Compressor LRA:	63	
EVAP CFM - High: EVAP Motor HP:	600 1/8	
COND CFM COND MOTOR HP	930 1/8	
Condensate Tank: Pump Optional	5 Gallon	
Refrigerant Charge:	40 oz R-410A	
Height: Width: Depth:	46.7″ 24″ 29.5″	
Net Weight:	260 lbs.	






Optional Accessories



Ceiling Panel Kit
For discharging the condenser air above a drop ceiling
Part Number: CK-12



Nozzle Kit / 2 x 6" For directional cooling Part Number: 2NK-2



Evaporator Return Air Plenum For ducting return air Part Number: 2DEP-12



Discharge Duct AdapterFor extended duct length
Part Number: 2DDA-10



Universal Condensate Pump KitFor unattended operation
Part Number: UPK-115



Condenser Return Air PlenumFor installations where it is required to duct air to the inlet of the condenser.
Part Number: 2DCP-2



OceanAire, Inc. 1731 Wall Street, Suite 100 Mount Prospect, Illinois 60056

OA-TS-PAC1811-01.03.22

