Model Number: OPAC14432AH



PROVIDING A BETTER CLIMATE ANYWHERE.





12-Ton Outdoor Rated Portable Air Conditioner

Product Features

REFRIGERATION

- 12-Ton Scroll Compressor
- Integrated Compressor Protection
- · Low Pressure and High Pressure Cut-out
- TXV Refrigeration Control with Hot Gas Bypass

ELECTRICAL

- CAM-LOK Power Connection
- · Heater Overload (Circuit Breakers)
- Phase Monitor Protection
- Control Wiring Circuit Breaker
- Analog Hour Meter

BLOWER/FILTERS

- Two Speed Evaporator Blower Package
- 2" Pleated Filters (3 Total, 18 x 20 x 2)
- Air Flow Pressure Switch Protection
- Reverse Curved Condenser Blower Package
- High Static Capability
- Low Ambient Fan Control

CABINET

- Through the Door Profile
- 2-Way Fork Pockets
- 8-Inch Urethane Swivel Casters with Locks
- Dual Handle Bars for Improved Mobility
- Duct Panels Evaporator

Supply: 2 x 16" dia. Flange Return: 2 x 16" dia. Flange

Condenser Discharge: 2 x 20" dia. Flange Return: Grille (Perforated Material)

Technical Specifications

Specifications subject to change without notice

Cooling Capacity: 144,000 BTUH Voltage: 208-230V, 60Hz, 3PH

Cooling Amps: 40
Heating Amps: 27
Total Watts: 13,300

Cooling Ambient: Operating Range 40° to 115°
Cooling Capacity: Total BTUH at 80°DB/67°WB

Return air 95°F Outdoor at high fan speed

EER: 10.8

Compressor: Scroll
Compressor HP: 12
Compressor RLA: 48.1
Compressor LRA: 245.0

Evaporator CFM - High: 4000

Blower Type: Twin Forward Curved Fans

Evaporator Motor: Two 1-HP each

Condenser Fan: Reverse Curved Impeller

COND CFM: 6250 COND Watts: 2400

Condensate Removal: Pump, 10 FT. LIFT Condensate Connection: 3/4" Male Garden Hose

Refrigerant Charge: 13 lbs. R410-A

Height: 77.0" Width: 72.25"

66.5" without handles Depth: 30.25"

Net Weight: 30.25

Optional: -B, CAM-LOK Buss Bar



OceanAire, Inc.

1731 Wall Street, Suite 100 Mount Prospect, Illinois 60056

OA-TS-OPAC14432AH-12.01.24

