Model Number: **OPAC14434**



PROVIDING A BETTER CLIMATE ANYWHERE.





12-Ton Outdoor Rated Portable Air Conditioner

Product Features:

REFRIGERATION

- 12-Ton Scroll Compressor
- Integrated Compressor Protection
- Low Pressure and High Pressure Cut-out
- TXV Refrigeration Control with Hot Gas Bypass

ELECTRICAL

- CAM-LOK Power Connection
- Phase Monitor Protection
- · Control Wiring Circuit Breaker
- Analog Hour Meter

BLOWER/FILTERS

- Two Speed Evaporator Blower Package
- 2-inch Pleated Filters (3 Total, 18 x 20 x 2)
- Reverse Curved Condenser Blower Package
- High Static Capability
- Low Ambient Fan Control

CABINET

- · Through the Door Profile
- 2-Way Fork Pockets
- * 8-Inch Urethane Swivel Casters with Locks
- · Dual Handle Bars for Improved Mobility
- Duct Panels Evaporator

Condenser Discharge: 2 x 20" dia. Flange Supply: 2 x 16" dia. Flange Return: 2 x 16" dia. Flange Return: Grille (Perforated Material)

Technical Specifications:

Specifications subject to change without notice

144,000 BTUH Cooling Capacity: 460V, 60Hz, 3PH Voltage: Amps: 17 Total Watts: 13,300 Cooling Ambient: Operating Range 40° to 115° Cooling Capacity: Total BTUH at 80°DB/67°WB Return air 95°F Outdoor at high fan speed EER: 10.8 Compressor: Scroll Compressor HP: 12 18.6 Compressor RLA: Compressor LRA: 125 Evaporator CFM - High: 4000 Blower Type: Twin Forward Curved Fans Two 1-HP each **Evaporator Motor:** Condenser Fan: Reverse Curved Impeller COND CFM: 6250 COND Watts: 2400 Condensate Removal: Pump, 10 FT. LIFT Condensate Connection: 3/4" Male Garden Hose Refrigerant Charge: 13 lbs. R410-A Height: 77.0" 72.25 Width: 66.5" without handles Depth: 30.25" Net Weight: 1273 lbs.



Optional:

OceanAire, Inc.

1731 Wall Street, Suite 100 Mount Prospect, Illinois 60056

OA-TS-OPAC14434-12.01.24



-B, CAM-LOK Buss Bar