Model Number:
OPACH4212

OceanAire
PROVIDING A BETTER CLIMATE ANYWHERE.

3.5-Ton Outdoor Portable Heat Pump with Auxiliary Heat

AIR COOLED

Product Features:

- 3.5 Ton Scroll Compressor
- Integrated Compressor Protection
- Low Pressure and High Pressure Cut-Out
- Locking 250V Power Connection Receptacle
- 50 Amp Circuit Breaker for Unit Power Protection
- 40 Amp Auxiliary Heat Breaker
- 24 VAC Thermostat with 50 ft. Detachable Cable
- Static Capability Up to 0.7” ESP
- 2” x 2” Steel Frame with Handle and Fork Pockets
- Wheel Pockets in Frame for Yard Storage (3 High - Max)
- 8-Inch Urethane Swivel Casters
- Supply: 1 x 12” Diameter Duct Collar
- Return: 2 x 12” Diameter Duct Collar with Integral Return Air Filter Frame
- Filter: (1) 14” x 25” x 1”, Pleated
- Drain: P-Trap with 3/4” Male garden Hose Connector

OPTIONAL

- 7 KW Electrical Heat for Low Temp Operation
- Automatic Heat Mode Change Over from HP to Aux. Heat

Technical Specifications:

Specifications subject to change without notice

Cooling Capacity:	40,500 BTUH
Heating Capacity:	37,600 BTUH
Aux. Heat Capacity:	7 KW
Voltage:	208-230V, 60Hz, 1PH
Amps:	31.8
Total Watts:	3780
Cooling Ambient:	Operating Range 25° to 115°
Cooling Capacity:	Total BTUH at 80°DB/67°WB Return air 95°F Outdoor
EER:	11.6
Compressor:	Scroll
Compressor HP:	3.5
Compressor RLA:	17.9
Compressor LRA:	112
Evaporator CFM - High:	1200
Evaporator Motor:	1/2 HP
Condenser Fan:	Propeller
COND CFM:	1750
Condenser Motor:	1/4 HP
Condensate Removal:	Gravity Drain
Refrigerant Charge:	132 ozs. R-410A
Height:	49.5″
Width:	75.5″ with handle
Depth:	42.0″
Net Weight:	670 lbs.

*Specifications subject to change without notice

OceanAire, Inc.
1731 Wall Street, Suite 100
Mount Prospect, Illinois 60056

OA-TS-OPACH4212-05.01.23

PROUDLY MADE IN THE USA

847.583.0311
oceanaire-inc.com